





Dent	entist Invoice Na					ame										
Invoi	Suburt				urb		ode _									
																_
							- /- l	h		l.s.d						_
BATCH # (Office only) Patie	nt ID - Please do	not use patient's name unless o	consent is provided,	and	арргорги	ate fori	n/s nave	been	compi	ietea.						
New Case Continuation/Remake	Ассоиг	t Number		V	Vork Rec	uired	ру		Da	ıy		Month				
PROSTHESIS TYPE	SHADE							J	CO	MPONE	NT SI	IPPI IF	R			
Crown Removable overdenture Bridge Locator Hybrid Bar & clip		○ Images to be emailed								0	Lab (def		0	Dent	ist	
IMPLANT		Teeth	1	18	17 16	15	14 13	3 12	11	21	22 2	3 24	25	26 2	27 2	28
System:		Platform Diameter														
For turnaround times please refer to price list.		Teeth		48	47 46	45	44 4	3 42	41	31	32 33	34	35	36 3	37	38
COMPONENT TYPES Genuine Parts Generic Parts		Platform Diameter														
(Incl. custom-milled abutment, Australian Made not available) STEP 2 Screw-Retained OR Cement STEP 3 PFM (non-precious alloy incl., other alloys n IPS E.MAX® Lab to assess and advise.	Most	RALIAN MADE (Ind. genuine) major brands accepted. //ith					(((Rac Rac FAST nsuffi	TRA cient o	ck phic cclus	a-based in a-based in al clearan ng and ma	ice ark on t	he mod		/ice	
SCREW-RETAINED "If Range has not been selected it will del	ault to SCD Range	CEMENT-RETAINED	μ,	d it will	default to SC	D Range		_			nent-reta					
SCD Range Quest Range Q	SCD Range Quest Range Q						ЛАТЕ	RIAL	ENC	LOSED						
Restoration Type PFM All-ceramic		Restoration Type PFM	All ceramic						tick (
○ Non-Precious ○ FMZir - Fully Monolith		○ Non-Precious	FMZir - Full A	Mon	olithic Z	irconia								DR	SCI	D
Semi-Precious* UZir - Ultra Translucer High-Precious* PFZ - Porcelain-Fused-		Semi-PreciousHigh-Precious	O IDS a may®	ain-F	used-to	-Zirco		nalog			/				\subset	
	to Zircoriia		○ IPS e.max®								lapt/Parts			_	C	
Ti Prz - Forcelain - Fused		^ SCD Range only	() Composite						<i>TT</i>							
☐ Ti ☐ IPS e.max® ☐ Genuine Cast ☐ Other		^ SCD Range only	Other						Impre	ssion				()	\sim	
 ☐ Ti ☐ IPS e.max® ☐ Genuine Cast ☐ Other ☐ Custom -Milled Ti* 		^ SCD Range only	· .				- L	pper							\subset)
☐ Ti ☐ IPS e.max® ☐ Genuine Cast ☐ Other		^ SCD Range only	· .				- L	ower pper	mpre: Mode	ssion I				🔾		
☐ Ti ☐ IPS e.max® ☐ Genuine Cast ☐ Other			Other	ine		ents)	- L	ower ower ower	mpre: Mode Model	ssion 					C)
Ti IPS e.max® Genuine Cast Other Custom -Milled Ti* ('default) ^ SCD Range only + Genuine Components only Alternative screw variations		Abutment type (choose ei Custom-milled Ge	Other			ents) ormed	- L L L B	ower ower ower ite Re	mpre: Mode Model gistrat	ssion tion (o	over prepa	red abu	ıtment)	0	CCC)
Ti IPS e.max® Genuine Cast Other Custom -Milled Ti* ('default) ^ SCD Range only + Genuine Components only Alternative screw variations (You will be advised if any limitations apply)		Abutment type (choose ei Custom-milled Go	Other ther custom or genuenuine Cast (specify alloy	y)	Prefo	ormed	- L L L B P	ower ower ower ower ower ower ower out the Re	mpres Mode Model gistrat us C &	ssion tion (o B to re	over prepa	ired abu	ıtment)		C	
Ti IPS e.max® Genuine Cast Other Custom -Milled Ti* ('default) ^ SCD Range only + Genuine Components only Alternative screw variations	nannel	Abutment type (choose ei	Other	y) s PFM	Prefo	ormed	– L L L B P	pper ower ower ite Re reviou	Impres Mode Model gistrat us C & us Stuc	ssion tion (o B to re	over prepa	ered abu	ıtment)			
Ti IPS e.max® Other Other Custom -Milled Ti* ("default) SCD Range only + Genuine Components only Alternative screw variations (You will be advised if any limitations apply) Cross screw Angled Screw Ch	annel	Abutment type (choose ei Custom-milled Go	ther custom or genuenuine Cast (specify alloy PFM default. Same alloy as	y) s PFM	Prefo	ormed	L L B P P P A	pper ower ower ite Re reviou reviou rticul	Mode Model gistrat us C & us Stuc ator	ssion I Lion (o B to re	over prepa eturn dels to ret	urn	utment)		0000000	
Ti IPS e.max® Genuine Cast Other Custom -Milled Ti* ('default) ^ SCD Range only + Genuine Components only Alternative screw variations (You will be advised if any limitations apply)	iannel	Abutment type (choose ei Custom-milled Go	ther custom or genuenuine Cast (specify alloy PFM default. Same alloy as	y) s PFM	Prefo	ormed	L L B P P C C C	pper ower ower ite Re reviou reviou rticul	Mode Model gistrat is C & is Stuc ator Bridg	ssion tion (a B to re dy Moo	over prepa eturndels to ret	urn	utment)			
Ti IPS e.max® Other Other Custom -Milled Ti* ("default) SCD Range only + Genuine Components only Alternative screw variations (You will be advised if any limitations apply) Cross screw Angled Screw Ch	annel	Abutment type (choose ei Custom-milled Go	ther custom or genuenuine Cast (specify alloy PFM default. Same alloy as	y) s PFM	Prefo	ormed	L L L L L L L L L L L L L L L L L L L	pper ower ower ite Re reviou reviou reticul entur rown, hade	Impre: Model Model gistrat is C & is Stuc ator /Bridg Tab	ssion I Lion (o B to re dy Moo	over prepa eturn dels to ret	urn	utment)			

PROMO CODE



Open Closed*





Heavy Light* Open

PROXIMAL CONTACT



Normal Extended*

PONTIC CONTACT



*0 0 0 0

*Default